

# MARINE CABLE

All cables are manufactured using oxygen free copper and RoHS compliant polyvinyl-chloride (V90 PVC) insulation in accordance with New Zealand Standard AS/NZS 5000.1. The Marine cable features the added benefit of tin coated copper strands for increased corrosion resistance.


## TWIN SHEATH CABLE

Part Number	No. of Cores	Cable DIA (mm)	Length (m)	AMPs	Conductor Cross Section (mm <sup>2</sup> )	Colour
5823M-100TW	2	3mm	100m	10A	1.13	Black, Red
5824M-100TW	2	4mm	100m	15A	1.84	Black, Red
5826M-100TW	2	6mm	100m	50A	4.59	Black, Red



## MULTICORE & TRAILER CABLE

Part Number	No. of Cores	Cable DIA (mm)	Length (m)	AMPs	Conductor Cross Section (mm <sup>2</sup> )	Colour
5834M-30WYB	3	4mm	30m	15A	1.84	White, Yellow, Brown
5852M-30ETC	5	2mm	30m	4A	0.5	Red, Green, Yellow, White, Brown
5853M-30TC	5	3mm	30m	10A	1	Red, Green, Yellow, White, Brown



## SINGLE CORE BATTERY CABLE

Part Number	No. of Cores	Cable DIA (B&S)	Length (m)	AMPs	Conductor Cross Section (mm <sup>2</sup> )	Colour
5808M-100BK	1	8 B&S	100m	100A*	10	Black
5806M-100BK	1	6 B&S	100m	140A*	16	Black
5803M-100BK	1	3 B&S	100m	215A*	25	Black
5802M-100BK	1	2 B&S	100m	255A*	35	Black



\*AMP rating based on a 60% duty cycle for 5 minutes

## SINGLE CORE CABLE

Part Number	No. of Cores	Cable DIA (mm)	Length (m)	AMPs	Conductor Cross Section (mm <sup>2</sup> )	Colour
5812M-30BK	1	2mm	30m	4A	0.5	Black
5812M-30RD	1	2mm	30m	4A	0.5	Red
5812M-30GN	1	2mm	30m	4A	0.5	Green
5812M-30YW	1	2mm	30m	4A	0.5	Yellow
5812M-30BE	1	2mm	30m	4A	0.5	Blue
5812M-30WE	1	2mm	30m	4A	0.5	White
5812M-30BN	1	2mm	30m	4A	0.5	Brown
5814M-30RD	1	4mm	30m	15A	1.84	Red
5814M-30BK	1	4mm	30m	15A	1.84	Black
5815M-100BK	1	5mm	100m	25A	2.9	Black
5816M-100RD	1	6mm	100m	50A	4.59	Red

