

# SAFETY DATA SHEET

## GUMOUT HIGH MILEAGE FUEL INJECTOR CLEANER

Infosafe No.: LQ96R  
ISSUED Date : 11/04/2019  
ISSUED by: Griffiths Equipment Ltd

### 1. IDENTIFICATION

#### GHS Product Identifier

GUMOUT HIGH MILEAGE FUEL INJECTOR CLEANER

#### Company Name

Griffiths Equipment Ltd

#### Address

22-24 Olive Road Penrose  
Auckland 1061 New Zealand

#### Telephone/Fax Number

Tel: +64 9 5254575

#### Emergency phone number

0800 764 766 (All Hours)

#### Emergency Contact Name

www.griffithsequipment.co.nz

#### E-mail Address

sales@griffithsequipment.co.nz

#### Recommended use of the chemical and restrictions on use

Fuel injector cleaner Consumer Use.

### 2. HAZARD IDENTIFICATION

#### GHS classification of the substance/mixture

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.  
Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

3.1D Flammable liquids: low hazard

6.1E (Aspiration hazard 1) - Substance that is acutely toxic

6.1E (Dermal) - Substance that is acutely toxic

6.3B Substance that is mildly irritating to the skin

6.7A Substance that is known or presumed to be a human carcinogen

6.9B (Repeated exposure) - Substance that is harmful to human target organs or systems

9.1B Substance that is ecotoxic in the aquatic environment

#### Signal Word (s)

DANGER

#### Hazard Statement (s)

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H313 May be harmful in contact with skin.

H316 Causes mild skin irritation.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure by oral and inhalation.

H411 Toxic to aquatic life with long lasting effects.

#### Pictogram (s)

Health hazard, Environment



**Precautionary statement – Prevention**

- P102 Keep out of reach of children.
- P103 Read label before use.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement – Response**

- P101 If medical advice is needed, have product container or label at hand.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P331 Do NOT induce vomiting.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P370+P378 In case of fire: Use Dry chemical, CO2, sand, earth, water spray or regular foam, alcohol resistant foam. for extinction.
- P391 Collect spillage.

**Precautionary statement – Storage**

- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

**Precautionary statement – Disposal**

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Ingredients**

| Name  | CAS        | Proportion |
|---|------------|------------|
| Distillates (petroleum), hydrotreated light | 64742-47-8 | 60-100 %   |
| Naphthalene                                 | 91-20-3    | 0.1-1 %    |
| Ingredients determined not to be hazardous  |            | Balance    |

**4. FIRST-AID MEASURES**

**Inhalation**

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

**Ingestion**

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

**Skin**

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

**Eye contact**

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

**First Aid Facilities**

Eyewash and normal washroom facilities.

**Advice to Doctor**

Treat symptomatically.

**Other Information**

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

---

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Dry chemical, CO<sub>2</sub>, sand, earth, water spray or regular foam, alcohol resistant foam.

**Unsuitable Extinguishing Media**

Do not use water jet.

**Hazards from Combustion Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

**Specific Hazards Arising From The Chemical**

Combustible. This product will burn if exposed to fire.

**Hazchem Code**

•3Z

**Decomposition Temperature**

Not available

**Precautions in connection with Fire**

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

---

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations.

If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

---

## 7. HANDLING AND STORAGE

**Precautions for Safe Handling**

Avoid exposure. Do not handle until all safety precautions have been read and understood.

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

**Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national

regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Naphthalene

TWA: 10 ppm, 52 mg/m<sup>3</sup>

STEL: 15 ppm, 79 mg/m<sup>3</sup>

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Source: Workplace Exposure Standards and Biological Exposure Indices.

### Biological Limit Values

Name: Naphthalene

Determinant: 1-Naphthol + 2-Naphthol

Value: -

Sampling time: End of shift

Notation: Nq, Ns

Source: American Conference of Industrial Hygienists (ACGIH)

### Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

### Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

### Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

### Hand Protection

Wear gloves of impervious material such as natural rubber, nitrile rubber, neoprene or PVC. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

### Body Protection

Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

| Properties                             | Description                   | Properties               | Description            |
|--|-------------------------------|--------------------------|------------------------|
| Form                                   | Liquid                        | Appearance               | Yellow liquid          |
| Colour                                 | Yellow                        | Odour                    | Hydrocarbon            |
| Decomposition Temperature              | Not available                 | Melting Point            | Not available          |
| Boiling Point                          | Not available                 | Solubility in Water      | Negligible             |
| Specific Gravity                       | Not available                 | pH                       | Not available          |
| Vapour Pressure                        | Not available                 | Vapour Density (Air=1)   | Not available          |
| Evaporation Rate                       | Not available                 | Odour Threshold          | Not available          |
| Viscosity                              | Not available                 | Volatile Component       | VOC content: 0.3%      |
| Partition Coefficient: n-octanol/water | Not available                 | Density                  | 0.83 g/cm <sup>3</sup> |
| Flash Point                            | > 84°C (Setaflash Closed Cup) | Flammability             | Combustible liquid     |
| Auto-Ignition Temperature              | Not available                 | Flammable Limits - Lower | Not applicable         |
| Flammable Limits - Upper               | Not applicable                |                          |                        |

## 10. STABILITY AND REACTIVITY

### Chemical Stability

Stable under normal conditions of storage and handling.

### Reactivity and Stability

Reacts with incompatibles.

### Conditions to Avoid

Heat, open flames and other sources of ignition.

### Incompatible materials

Strong oxidising agents.

### Hazardous Decomposition Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon oxides.

### Possibility of hazardous reactions

Not available

### Hazardous Polymerization

Not available

## 11. TOXICOLOGICAL INFORMATION

### Toxicology Information

The available toxicity data available for this material and the available acute toxicity data for the ingredients are given below.

### Acute Toxicity - Oral

ATEmix: 5,268 mg/kg

Distillates (petroleum), hydrotreated light

LD50 (Rat): > 5,000 mg/kg

Naphthalene

LD50 (Rat): 1,110 mg/kg

LD50 (Rat): 490 mg/kg

**Acute Toxicity - Inhalation**

Distillates (petroleum), hydrotreated light  
LC50 (Rat): > 5.2 mg/L/4h

Naphthalene

LC50 (Rat): >340 mg/m<sup>3</sup>/1h

**Acute Toxicity - Dermal**

ATEmix: 2,107 mg/kg

Distillates (petroleum), hydrotreated light  
LD50 (Rabbit): > 2,000 mg/kg

Naphthalene

LD50 (Rabbit): 1120 mg/kg

LD50 (Rabbit): > 20 g/kg

**Ingestion**

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

**Inhalation**

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

**Skin**

May be harmful in contact with skin. Product can be absorbed through skin with resultant harmful systemic effects. Causes mild skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

**Eye**

May be irritating to eyes. The symptoms may include redness, itching and tearing.

**Respiratory sensitisation**

Not expected to be a respiratory sensitiser.

**Skin Sensitisation**

Not expected to be a skin sensitiser.

**Germ cell mutagenicity**

Not considered to be a mutagenic hazard.

**Carcinogenicity**

May cause cancer. Classified as a Known or presumed human carcinogen.

Naphthalene is listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC).

**Reproductive Toxicity**

Not considered to be toxic to reproduction.

**STOT-single exposure**

Not expected to cause toxicity to a specific target organ.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure by oral and inhalation.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

**12. ECOLOGICAL INFORMATION**

---

**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

**Persistence and degradability**

Not available

**Mobility**

Disperses in water.

Naphthalene

Partition coefficient: 3.6

**Bioaccumulative Potential**

Not available

**Other Adverse Effects**

Not available

**Environmental Protection**

Do not discharge this material into waterways, drains and sewers.

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal considerations**

Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a combustible substance and therefore can be sent to an approved high temperature incineration plant for disposal.

Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.

Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected.

In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal:

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

## 14. TRANSPORT INFORMATION

---

**Transport Information**

Road and Rail (New Zealand):

This material is classified as a Class 9 – Miscellaneous Substances

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1: Explosives

Class 9 dangerous goods that contain organic matter must not be loaded in the same bulk container or tankwagon with dangerous goods of Division 5.1 unless the Class 9 and Division 5.1 dangerous goods are in separate compartments of a bulk container or tankwagon.

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices. Segregation devices may be used to segregate Dangerous goods of Class 9 when the nature of those dangerous goods requires them to be segregated from dangerous goods of Class 3, 4, 5, 6 or 8 or from food items.

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 9

UN No: 3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Distillates (petroleum), hydrotreated light) (MARINE POLLUTANT)  
Packing Group: III  
EMS: F-A, S-F  
Special Provisions: 274 335 969

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 9

UN No: 3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Distillates (petroleum), hydrotreated light)

Packing Group: III

Packaging Instructions (passenger & cargo): 964

Packaging Instructions (cargo only): 964

Hazard Label: Miscellaneous

Special Provisions: A97, A158, A197

**U.N. Number**

3082

**UN proper shipping name**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(Contains Distillates (petroleum), hydrotreated light)

**Transport hazard class(es)**

9

**Packing Group**

III

**Hazchem Code**

•3Z

**IERG Number**

47

**IMDG Marine pollutant**

Yes

**Transport in Bulk**

Not available

**Special Precautions for User**

Not available

## 15. REGULATORY INFORMATION

---

**Regulatory information**

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Group Standard: Fuel Additives (Combustible, Toxic [6.7]) Group Standard 2006.

**HSNO Approval Number**

HSR002587

## 16. OTHER INFORMATION

---

**Date of preparation or last revision of SDS**

SDS created: April 2018

**References**

Workplace Exposure Standards and Biological Exposure Indices.

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Assigning a hazardous substance to a group standard.



Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

## END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.