# **SAFETY DATA SHEET**

# **BLACK MAGIC INTENSE TIRE WET**

Infosafe No.: LQ98G ISSUED Date : 14/01/2019 ISSUED by: Griffiths Equipment Ltd

#### **1. IDENTIFICATION**

GHS Product Identifier BLACK MAGIC INTENSE TIRE WET

**Company Name** Griffiths Equipment Ltd

Address 22-24 Olive Road Penrose Auckland 1061 New Zealand

**Telephone/Fax Number** Tel: +64 9 5254575

**Emergency phone number** 0800 764 766 (All Hours)

Emergency Contact Name www.griffithsequipment.co.nz

E-mail Address sales@griffithsequipment.co.nz

**Recommended use of the chemical and restrictions on use** Tire Dressing

### 2. HAZARD IDENTIFICATION

#### GHS classification of the substance/mixture

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand. Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

3.1D Flammable liquids: low hazard

6.1E (Aspiration hazard 1) - Substance that is acutely toxic

6.1E (Dermal) - Substance that is acutely toxic

6.3B Substance that is mildly irritating to the skin

9.1A Substance that is very ecotoxic in the aquatic environment

9.4A Substance that is very ecotoxic to terrestrial invertebrates

Signal Word (s) DANGER

#### Hazard Statement (s)

H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H313 May be harmful in contact with skin.
H316 Causes mild skin irritation.
H410 Very toxic to aquatic life with long lasting effects.
H441 Very toxic to terrestrial invertebrates.

#### Pictogram (s)

Environment, Health hazard



#### **Precautionary statement – Prevention**

P102 Keep out of reach of children. P103 Read label before use. P104 Read Safety Data Sheet before use. P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. **Precautionary statement – Response** P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P101 If medical advice is needed, have product container or label at hand. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331 Do NOT induce vomiting. P332+P313 If skin irritation occurs: Get medical advice/attention. P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam for extinction. P391 Collect spillage.

#### Precautionary statement – Storage

P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

#### **Precautionary statement – Disposal**

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Ingredients

Name	CAS	Proportion
Distillates (petroleum), hydrotreated light	64742-47-8	30-60 %
Siloxanes and silicones, dimethyl	63148-62-9	10-30 %
Ingredients determined not to be hazardous		Balance

#### **4. FIRST-AID MEASURES**

#### Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

#### Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

#### Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

#### Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

#### **First Aid Facilities**

Eyewash, safety shower and normal washroom facilities.

#### Advice to Doctor

Treat symptomatically.

#### **Other Information**

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

#### **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Use carbon dioxide, dry chemical or foam.

#### **Hazards from Combustion Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon oxides.

#### Specific Hazards Arising From The Chemical

Combustible. This product will burn if exposed to fire.

Hazchem Code

•3Z

#### **Decomposition Temperature**

Not available

#### Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

### **6. ACCIDENTAL RELEASE MEASURES**

#### **Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

### 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

#### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Occupational exposure limit values**

No exposure standards have been established for this material, however, the TWA exposure standards for oil mist (mineral) is 5 mg/m<sup>3</sup>, STEL: 10 mg/m<sup>3</sup>. As with all chemicals, exposure should be kept to the lowest possible levels.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-

hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Source: Workplace Exposure Standards and Biological Exposure Indices.

#### **Biological Limit Values**

No biological limits allocated.

#### **Appropriate Engineering Controls**

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

#### **Respiratory Protection**

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

#### **Eye Protection**

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/ face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

#### **Hand Protection**

Wear gloves of impervious material such as natural rubber, nitrile rubber, Neoprene<sup>™</sup> or PVC gloves. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

#### **Body Protection**

Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Properties	Description	Properties	Description
Form	Liquid	Appearance	Clear liquid
Colour	Clear	Odour	Cherry
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	>100 °C	Solubility in Water	Disperses in water.
рН	Not available	Vapour Pressure	Not available
Vapour Density (Air=1)	Not available	Evaporation Rate	Not available
Odour Threshold	Not available	Viscosity	Not available
Volatile Component	VOC content: 1.0%	Partition Coefficient: n- octanol/water	Not available
Density	<1	Flash Point	80°C (Setaflash Closed Cup)
Flammability	Combustible liquid	Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not applicable	Flammable Limits - Upper	Not applicable
Relative density	7.16 (25°C)		

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### **10. STABILITY AND REACTIVITY**

#### **Chemical Stability**

Stable under normal conditions of storage and handling.

**Reactivity and Stability** Reacts with incompatibles.

**Conditions to Avoid** Heat, open flames, sparks and other sources of ignition.

**Incompatible materials** Strong oxidising agents.

Hazardous Decomposition Products Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon oxides.

**Possibility of hazardous reactions** None under normal processing.

Hazardous Polymerization

Not available

#### **11. TOXICOLOGICAL INFORMATION**

#### **Toxicology Information**

The available toxicity data available for this material and the available acute toxicity data for the ingredients are given below.

Acute Toxicity - Oral ATEmix: 5,474 mg/kg

Distillates (petroleum), hydrotreated light LD50 (Rat): > 5,000 mg/kg

Siloxanes and silicones, dimethyl LD50 (Rat): > 17 g/kg LD50 (Rat): > 24 g/kg

Acute Toxicity - Inhalation Distillates (petroleum), hydrotreated light

LC50 (Rat): > 5.2 mg/L/4h Acute Toxicity - Dermal ATEmix: 2,004 mg/kg

Distillates (petroleum), hydrotreated light LD50 (Rabbit): > 2,000 mg/kg

Siloxanes and silicones, dimethyl LD50 (Rabbit): > 2 g/kg

#### Ingestion

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

#### Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

Causes mild skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

#### Eye

May be irritating to eyes. The symptoms may include redness, itching and tearing.

#### **Respiratory sensitisation**

Not expected to be a respiratory sensitiser.

#### **Skin Sensitisation** Not expected to be a skin sensitiser.

**Germ cell mutagenicity** Not considered to be a mutagenic hazard.

**Carcinogenicity** Not considered to be a carcinogenic hazard.

**Reproductive Toxicity** Not considered to be toxic to reproduction.

**STOT-single exposure** Not expected to cause toxicity to a specific target organ.

**STOT-repeated exposure** Not expected to cause toxicity to a specific target organ.

# Aspiration Hazard

May be fatal if swallowed and enters airways.

## **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

Very toxic to aquatic life with long lasting effects and very toxic to terrestrial invertebrates.

Persistence and degradability Not available

**Mobility** Disperses in water.

**Bioaccumulative Potential** Not available

Other Adverse Effects Not available

**Environmental Protection** Do not discharge this material into waterways, drains and sewers.

### **13. DISPOSAL CONSIDERATIONS**

#### **Disposal considerations**

#### Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a combustible substance and therefore can be sent to an approved high temperature incineration plant for disposal.

Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.

Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected.

In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal:

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-

hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

#### **14. TRANSPORT INFORMATION**

#### Transport Information

Road and Rail (New Zealand):

This material is classified as a Class 9 – Miscellaneous Substances

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1: Explosives

Class 9 dangerous goods that contain organic matter must not be loaded in the same bulk container or tankwagon with dangerous goods of Division 5.1 unless the Class 9 and Division 5.1 dangerous goods are in separate compartments of a bulk container or tankwagon.

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices. Segregation devices may be used to segregate Dangerous goods of Class 9 when the nature of those dangerous goods requires them to be segregated from dangerous goods of Class 3, 4, 5, 6 or 8 or from food items.

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 9 UN No: 3082 Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Distillates (petroleum), hydrotreated light) (MARINE POLLUTANT) Packing Group: III EMS: F-A, S-F Special Provisions: 274 335 969

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. Class/Division: 9 UN No: 3082 Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Distillates (petroleum), hydrotreated light) Packing Group: III Packaging Instructions (passenger & cargo): 964 Packaging Instructions (cargo only): 964 Hazard Label: Miscellaneous Special Provisions: A97, A158, A197

**U.N. Number** 3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(Contains Distillates (petroleum), hydrotreated light)

Transport hazard class(es) 9 Packing Group III Hazchem Code • 3Z IERG Number 47 IMDG Marine pollutant Yes

#### Transport in Bulk Not available

**Special Precautions for User** Not available

#### **15. REGULATORY INFORMATION**

#### **Regulatory information**

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand. Group Standard: Additives, Process Chemicals and Raw Materials (Combustible) Group Standard 2006.

#### HSNO Approval Number

HSR002490

#### **16. OTHER INFORMATION**

#### Date of preparation or last revision of SDS

SDS created: January 2019

#### References

Workplace Exposure Standards and Biological Exposure Indices.

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Assigning a hazardous substance to a group standard.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

# END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.